

# INDEX

Vol. 1 No. 1 through Vol. 5 No. 6

## Audio Equipment

Audio Oscillator	Vol. 3 No. 2 p. 1
Logarithmic Compressor	Vol. 5 No. 3 p. 1
Mobile Modulator	Vol. 5 No. 4 p. 1
Restricted Range Speech Amplifier	Vol. 4 No. 5 p. 1
Six Watt Miniature Tube Audio Amplifier	Vol. 1 No. 3 p. 1

## Designer's Corner

Capacitive Interstage Coupling	Vol. 5 No. 2 p. 6
Design of the SSB, Jr. Rig	Vol. 5 No. 6 p. 10
Equipment Design	Vol. 5 No. 5 p. 8

## Miscellaneous

Dx Log (Official Country and Prefix List)	Vol. 2 No. 2 p. 1
Frequency Chart	Vol. 2 No. 5 p. 6
Mobile and Emergency Antenna	Vol. 5 No. 4 p. 5
Rules for BERTA, DXCC, WAC, WAS, WAZ, WBE	Vol. 2 No. 3 p. 5
Rules for WAVE	Vol. 3 No. 2 p. 7
Selenium Rectifier Data	Vol. 3 No. 3 p. 8
Table-top Antennas	Vol. 4 No. 1 p. 1

## Power Supplies

Selenium Rectifier Power Supplies	Vol. 3 No. 3 p. 5
Thyratron Rectifiers for Keying and Variable Output	Vol. 1 No. 2 p. 1

## Questions and Answers

Battery-Operated Tubes	Vol. 4 No. 5 p. 6
Class B Audio vs. Class C R-F Applied Voltages	Vol. 1 No. 2 p. 3
C-R Tube Numbering	Vol. 4 No. 5 p. 6
C-R Tube Operation	Vol. 4 No. 3 p. 6
Current Surge in 117Z6 Filament	Vol. 2 No. 1 p. 3
Discoloring of Bulbs	Vol. 4 No. 3 p. 6
Driving Power	Vol. 3 No. 5 p. 7
Driving Power and Amplification Factor Relationship	Vol. 1 No. 4 p. 3
Driving Power Computations	Vol. 2 No. 4 p. 6
Filament Voltage Variation vs Tube Life	Vol. 2 No. 4 p. 6
Final Tank Tuning	Vol. 1 No. 1 p. 3
Fluorescent Lamp Interference	Vol. 5 No. 5 p. 5
Frequency for Typical Data	Vol. 3 No. 4 p. 7
Frequency Limitation of Tubes	Vol. 1 No. 3 p. 3
Getter in Tubes	Vol. 4 No. 1 p. 7
Glass to Metal Seals	Vol. 4 No. 3 p. 6
Glass Tube Numbers	Vol. 4 No. 5 p. 6
Glow in 866 Rectifiers with No Voltage Applied	Vol. 1 No. 2 p. 3
Grid Drive Variation	Vol. 2 No. 5 p. 7
Grid Resistor and Battery Bias	Vol. 1 No. 4 p. 3
Low-Loss Sockets	Vol. 4 No. 1 p. 7
Maximum Grid Resistance	Vol. 4 No. 2 p. 6
Maximum Ratings and Typical Operation	Vol. 5 No. 5 p. 2
Meaning of IC on Socket Connection Diagram	Vol. 2 No. 4 p. 6
Metal vs. Glass Tubes	Vol. 4 No. 3 p. 6
Neutralization with One Condenser	Vol. 1 No. 1 p. 3
Overdriving a Class C Stage	Vol. 2 No. 4 p. 6
Plate-to-Plate Impedance for Parallel Audio Tubes	Vol. 2 No. 1 p. 3
Receiver Tube Testing	Vol. 3 No. 5 p. 7
Repairing Loose Anode Caps	Vol. 5 No. 5 p. 3
Shelf Life and Operating Position of Tubes	Vol. 1 No. 3 p. 3
Standby Operation	Vol. 3 No. 4 p. 7
Storing Spare Tubes	Vol. 3 No. 4 p. 7
Suffix "W"	Vol. 4 No. 5 p. 6
Testing V-R Tubes	Vol. 4 No. 2 p. 6
Tube Data Calculation	Vol. 4 No. 1 p. 7
Tube Filament Power	Vol. 4 No. 1 p. 7
Tube Operating Position	Vol. 4 No. 2 p. 6
Tube Operation with No Plate Voltage Applied	Vol. 2 No. 5 p. 7
V-R Tube Jumpers	Vol. 3 No. 4 p. 7
V-R Tubes in Parallel	Vol. 4 No. 3 p. 7

## Reception

Guillotine Converter (for Six and Ten Meters)	Vol. 2 No. 4 p. 1
R-9'er (One Tube Preamplifier)	Vol. 1 No. 4 p. 1
	Vol. 2 No. 1 p. 5
Single Sideband Reception	Vol. 3 No. 6 p. 1

## Technical Tidbits

Caution—Screen Grid at Work	Vol. 3 No. 4 p. 4
-----------------------------	-------------------

High-Frequency R-F Chokes	Vol. 4 No. 1 p. 5
Proper Plate Tank Padding	Vol. 3 No. 5 p. 6
Proper Tank Circuit and Antenna Coupling Adjustments	Vol. 3 No. 2 p. 8
Restricting Speech Range in Speech Amplifiers	Vol. 4 No. 4 p. 6
Why Forced-Air Cooling?	Vol. 2 No. 1 p. 6
Wiring Techniques	Vol. 3 No. 4 p. 5

## Test and Measuring Equipment

Audio Oscillator	Vol. 3 No. 2 p. 1
Frequency Standard	Vol. 4 No. 3 p. 1
Modulation Monitor	Vol. 3 No. 2 p. 5
Selenium Rectifier Utility Power Supply	Vol. 3 No. 3 p. 6
Volt-ohmmeter	Vol. 3 No. 2 p. 3

## Transmitting Equipment

Economy Half-Kilowatt	Vol. 3 No. 5 p. 1
Emergency-Portable Rig	Vol. 5 No. 2 p. 1
Five-Band VFO	Vol. 2 No. 6 p. 1
	Vol. 3 No. 2 p. 4
GL-837 Oscillator-Doubler	Vol. 2 No. 3 p. 2
Harmoniker (Half-wave Filter for TVI Elimination)	Vol. 4 No. 6 p. 1
Lazy Linear (Final for AM, NBFM, CW or SSB)	Vol. 4 No. 4 p. 1
MHE Transmitter (Six and Ten Meter Mobile Rig)	Vol. 4 No. 2 p. 1
Mobile Modulator	Vol. 5 No. 4 p. 1
One Kilowatt—One Chassis (GL-8000's in Final)	Vol. 2 No. 1 p. 1
One-Tube Keying Monitor	Vol. 2 No. 3 p. 4
One-Tube 420 mc Transmitter	Vol. 4 No. 1 p. 1
Push-Pull GL-813 Ten Meter Final	Vol. 1 No. 1 p. 1
Remote Control by Carrier Current	Vol. 3 No. 3 p. 2
	Vol. 3 No. 4 p. 4
Rig-Builder's Circuit Guide	Vol. 3 No. 1 p. 1
SSB, Jr. (Three Tube SSB Rig)	Vol. 5 No. 6 p. 1
VFO Design and Construction	Vol. 2 No. 5 p. 1

## Tricks and Topics

Antenna De-Icer	Vol. 2 No. 4 p. 7
Antenna Element Strengtheners	Vol. 5 No. 5 p. 2
Automatic Lightning Protection	Vol. 5 No. 5 p. 4
Bias Supply	Vol. 1 No. 3 p. 3
Bleeder Economy	Vol. 4 No. 2 p. 6
Cleaning Old Sockets	Vol. 4 No. 5 p. 5
Coaxial Antenna Connector	Vol. 5 No. 5 p. 6
Crystal Socket Trick	Vol. 1 No. 2 p. 3
Crystal Stretching	Vol. 3 No. 5 p. 7
D-c Relay Trick	Vol. 2 No. 4 p. 7
Economical QSL Card	Vol. 5 No. 5 p. 3
Dynamic Speaker Field Power Supply	Vol. 5 No. 5 p. 6
Eyelet Holder	Vol. 3 No. 4 p. 6
Extra-rigid Coil Mounting	Vol. 5 No. 5 p. 5
Home-Made Coil Dope	Vol. 4 No. 1 p. 7
Improving a Bug	Vol. 4 No. 2 p. 6
Improving a Straight Key	Vol. 4 No. 2 p. 6
Index Marking for Call Book	Vol. 4 No. 3 p. 7
Joint Unsoldering	Vol. 4 No. 5 p. 5
Make Your Own Insulators	Vol. 1 No. 1 p. 3
Metal Chassis Preserver	Vol. 1 No. 4 p. 3
Meter Shunt Trick	Vol. 1 No. 2 p. 3
Microphone Cover	Vol. 5 No. 3 p. 8
Mounting Feet	Vol. 2 No. 4 p. 7
Neutralizing Trick	Vol. 1 No. 2 p. 3
Noiseless Slip Rings	Vol. 3 No. 4 p. 6
Non-Slip Equipment	Vol. 3 No. 5 p. 7
Panel Marking Trick	Vol. 2 No. 5 p. 7
Pilot Bulb Removal	Vol. 2 No. 4 p. 7
Plug-in Variable Link	Vol. 3 No. 4 p. 6
Proper Care of Crystal Microphone	Vol. 5 No. 3 p. 7
QRP Trick	Vol. 1 No. 3 p. 3
QSL Card Display	Vol. 3 No. 4 p. 6
Refinishing Panels	Vol. 4 No. 5 p. 5
Resonant Receiver Choke	Vol. 1 No. 4 p. 3
R-F Choke	Vol. 1 No. 3 p. 3
R-F Indicator	Vol. 4 No. 1 p. 7
R-F Indicator Trick	Vol. 2 No. 5 p. 7
Rotary Joint for Beams	Vol. 4 No. 3 p. 7
Screen Grid Keying	Vol. 3 No. 2 p. 7
Socket Wiring Trick	Vol. 2 No. 1 p. 7
Soldering Trick	Vol. 2 No. 4 p. 7
Thin-Wall Conduit Stunts	Vol. 1 No. 1 p. 3
Tune-up Trick	Vol. 2 No. 4 p. 7
Universal Crystal Socket	Vol. 2 No. 1 p. 7
Variable Condenser Trick	Vol. 3 No. 5 p. 7
VFO HI-LO Switch	Vol. 5 No. 3 p. 7
Wire Covering	Vol. 5 No. 3 p. 7



Tube Data					
6AK5.....	Vol. 1 No. 4 p. 4	35W4.....	Vol. 1 No. 3 p. 4		
	Vol. 2 No. 4 p. 8	50B5.....	Vol. 1 No. 3 p. 4		
	Vol. 4 No. 3 p. 8	FG-17.....	Vol. 1 No. 2 p. 4		
6AG7.....	Vol. 5 No. 6 p. 12	GL-2E26.....	Vol. 4 No. 2 p. 8		
6AK6.....	Vol. 5 No. 2 p. 8	GL-4D21/4-125A.....	Vol. 3 No. 2 p. 8		
6BE6.....	Vol. 2 No. 4 p. 8	GL-807.....	Vol. 2 No. 6 p. 8		
6C4.....	Vol. 1 No. 3 p. 4	GL-813.....	Vol. 1 No. 1 p. 4		
	Vol. 2 No. 4 p. 8	GL-837.....	Vol. 2 No. 3 p. 8		
6X4.....	Vol. 2 No. 4 p. 8		Vol. 2 No. 5 p. 8		
12AT6.....	Vol. 1 No. 3 p. 4	GL-8000.....	Vol. 2 No. 1 p. 8		
12AT7.....	Vol. 4 No. 1 p. 8				
12AU7.....	Vol. 5 No. 4 p. 8				
12AX7.....	Vol. 4 No. 5 p. 8				
12BA6.....	Vol. 1 No. 3 p. 4				
		VHF Equipment			
		Megaboooster (420 mc. Final).....	Vol. 3 No. 4 p. 1		
		One-Tube 420 mc. Transmitter.....	Vol. 4 No. 1 p. 1		

#### VHF Equipment

Megabooster (420 mc. Final).....	Vol. 3 No. 4 p. 1
One-Tube 420 mc. Transmitter.....	Vol. 4 No. 1 p. 1

## ERRATA

### Vol. 1 No. 3 p. 4

Tube basing diagram shown for 50B5 should be used for 12BA6 and vice versa.

### Vol. 2 No. 6 p. 5

The circuit diagram as shown shorts the B plus voltage to ground. One switch section has been omitted in the GL-807 plate circuit. The omitted section is S-II and it is contained on the same switch pie as S-IG. Both leads from the right-hand side of  $M_2$  should be eliminated. The pole of S-II connects to the right-hand side of  $M_2$  and each of the five switch positions is wired to the bottom end of the corresponding tank coil.

### Vol. 3 No. 1

In the circuit diagrams on pages 4 and 5, omit the 0.01 mf condenser which connects between the center of the grid coil and ground.

### Vol. 3 No. 3

Fig. 4, page 3, is in error. The lead going from the top of  $R_1$  to  $C_1$  should be removed from  $C_1$  and wired instead to the bottom of the secondary of  $T_2$ . The  $C_1$  lead from the bottom of  $R_6$  to the top of  $R_7$  should be replaced with a direct connection. The lead going from  $R_1$  to the bottom of  $R_6$

should be rewired so that it connects  $R_1$  to the top of  $R_6$ .

### Vol. 3 No. 6

(1) Switch  $S_2$  in Fig. 2 need only be a three-pole four-position switch. To change circuit connect the arm of  $R_{21}$  to position 2 on section F. Connect the bottom end of  $R_{22}$  to position 3 on section F. Connect the arm of  $R_{21}$  to position 4 on section F. Remove wiring from sections C, D and E, making certain that the pole of section F still connects to the grid of the 6C4. (2) In Fig. 2, the "black" wire of  $L_2$  should be marked "green" and the "green" wire marked "black." (3) On page 4, second column, line 16, the 24 mmf condenser mentioned is a mica condenser. Please note that some Millen 60456 transformers do not contain this mica condenser and in this case the transformer should tune as it is. (The tap change described on lines 13 and 14 should still be made.) (4) On page 7, first column, line 23, "50,000 ohm condenser" should read "50,000 ohm resistor."

### Vol. 5 No. 2

Under Circuit Constants on page 2, " $R_1, R_2, R_2, R_2$ " should read " $R_1, R_2, R_2, R_1$ ."

### Vol. 5 No. 6

Under Circuit Constants on page 6, the second line should read " $C_2, C_3$ " not " $C_2, C_1$ ."